

WHAT IS CLAIMED IS:

1. A sound-correction system in the audio apparatus installed in a vehicle, comprising:

a music-adjustment device which corrects the sound; and

5 a noise-information-detection device which detects noise information; and wherein said music-adjustment device corrects the sound according to the noise level detected by said noise-information-detection device.

10 2. The sound-correction system of claim 1 wherein said noise-information-detection device comprises an extraction device which extracts low-frequency-noise level that occurs from the vehicle; and wherein

said music-adjustment device corrects the sound based
15 on said detected low-frequency-noise level.

3. The sound-correction system of claim 1 wherein said noise-information-detection device comprises a first detection device which detects the vehicle speed; and
20 wherein

said music-adjustment device corrects the sound based on said detected vehicle speed.

4. The sound-correction system of claim 1 wherein
25 said noise-information detection device comprises a second detection device which detects opened/closed information of an opening/closing mechanism of the vehicle;

and wherein

said music-adjustment device corrects the sound based on said detected opened/closed information.

5 5. The sound-correction system of claim 1 wherein
said noise-information-detection device comprises a third-detection device which detects the music level; and wherein

10 said music-adjustment device corrects the sound based on said detected music level.

6. The sound-correction system of claim 1 wherein
said music-adjustment device comprises: a low-frequency-correction device which corrects
15 low-frequency sound, a high-frequency-correction device which corrects high-frequency sound, and a full-range-correction device which corrects full-range sound.

7. The sound-correction system of claim 6 wherein
20 said low-frequency-correction device corrects the sound based on the low-frequency noise detected by said extraction device.

8. The sound-correction system of claim 6 wherein
25 said high-frequency-correction device corrects the sound based on the vehicle speed detected by said first detection device, and the opened/closed information detected by said

second detection device.

9. The sound-correction system of claim 6 wherein
said full-range correction device corrects the sound
5 based on the vehicle speed detected by said first detection
device, and the opened/closed information detected by said
second detection device.

10. A recording medium which is readable by a computer
10 included in a sound-correction system of an audio apparatus
installed in a vehicle, and on which a sound-correction program
is recorded, where in the program causes the computer to
function as

a music-adjustment device which corrects the sound; and
15 as

a noise-information-detection device which detects noise
information; and wherein

said music-adjustment device corrects the sound according
to the noise level detected by said
20 noise-information-detection device.

11. A sound-correction method in the audio apparatus
installed in a vehicle comprising:

a music-adjustment process of correcting the sound; and
25 a noise-information-detection process for detecting
noise information; and wherein

said music-adjustment process corrects the sound

according to the noise level detected by said noise-information-detection process.

12. A sound-correction apparatus in the audio apparatus
5 installed in a vehicle comprising:

an adjustment device adjusting the sound-volume in the full frequency range of the reproduced signal;

a low-frequency-correction device which corrects the sound in the low-frequency range;

10 a high-frequency-correction device which corrects sound in the high-frequency range;

an extraction device that extracts the low-frequency component below the audible frequency;

a first detection device that detects the vehicle speed;

15 a second detection device that detects the opened/closed status of the opening/closing function in the vehicle;

a third detection device which detects the amount of adjustment by said adjustment device;

a first calculation device that calculates the amount
20 of low-frequency correction that is corrected by said low-frequency-correction device according to the ratio of said low-frequency component extracted by said extraction device, and said adjustment amount detected by said third detection device ; and

25 a second calculation device that calculates the amount of high-frequency correction that is corrected by said high-frequency-correction device according to said detected

vehicle speed, said detected opened/closed status and said detected adjustment amount.

13. The sound-correction apparatus of claim 12
5 comprising:

a memory device that stores said amount of low-frequency correction in correspondence to the ratio of said low-frequency component extracted by said extraction device, and said amount of adjustment detected by said third detection
10 device, and stores said amount of high-frequency correction in correspondence to said detected adjustment amount, said vehicle speed and said opened/closed status; and wherein
said low-frequency-correction device performs correction based on said amount of low-frequency correction
15 stored in said memory device , and
said high-frequency-correction device performs correction based on said amount of high-frequency correction stored in said memory device.

20 14. The sound-correction apparatus of claim 12 wherein
said amount of low-frequency correction increases with respect to said adjustment amount detected by said third detection device according as the level of said low-frequency component extracted by said extraction device increases.

25

15. The sound-correction apparatus of claim 12 wherein
said amount of low-frequency correction is the amount

that the sound of frequencies below a specified frequency is corrected, and it increases according as the frequency is lower.

5 16. The sound-correction apparatus of claim 12 wherein
 said amount of high-frequency correction is the amount
that the sound in the full range of the signal being reproduced
is corrected, and it increases according as the frequency
is higher.

10

 17. The sound-correction apparatus of claim 12 wherein
 said amount of high-frequency correction increases
according as said vehicle speed increases.

15

 18. The sound-correction apparatus of claim 12 wherein
 when said opening/closing mechanism is opened, said
amount of high-frequency correction increases with respect
to said amount of high-frequency correction when said
opening/closing mechanism is closed.

20

 19. The sound-correction apparatus of claim 12 wherein
 said amount of high-frequency correction decreases
according as said adjustment amount detected by said third
detection device increases.

25

 20. A sound-correction method for the audio apparatus
installed in a vehicle having an adjustment process of

adjusting the sound volume of the full frequency range of the signal being reproduced, comprising:

an extraction process of extracting the low-frequency component below the audible frequency;

5 a first detection process of detecting the vehicle speed;

a second detection process of detecting the opened/closed status of an opening/closing mechanism in the vehicle;

a third detection process of detecting the adjustment amount by said adjustment process;

10 an acquisition process of acquiring the ratio of said low-frequency component extracted by said extraction process and said adjustment amount detected by said third detection process;

15 a first calculation process of calculating the low-frequency-correction characteristics according to the ratio calculated by said acquisition process;

a second calculation process of calculating the high-frequency-correction characteristics according to said adjustment amount, said vehicle speed and said opened/closed status;

20 a low-frequency-correction process of correcting the sound in the low-frequency range based on said low-frequency-correction characteristics calculated by said first calculation process; and

25 a high-frequency-correction process of correcting the sound in the high-frequency range based on said high-frequency-correction characteristics calculated by

said second calculation process.